



SAE 15W40

140102101



GOLD PLATINUM SN/CF SAE 15W40

This product is a very advanced mineral engine oil that has been developed for gasoline and diesel engines. This product is made of the finest European base oils and additives. This product meets and exceeds many of the industry and OEM specifications required by newer modern gasoline and diesel powered automobile engines. This

product has active cleaning agents that help to reduce the deposit and sludge build up in the engine. This product can be recommended for all types of modern vehicles including vehicles with turbochargers, superchargers and multi-valve injected engines.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,873
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	107
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	14,2
Viscosity Index	ASTM D2270		135
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,2
Pour point	ASTM D6892	°C	-36
Flash point	ASTM D92	°C	215
Sulphated ash content	ASTM D874	%	0,96
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	7000
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	
CCS viscosity @ -35 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA A3/B4
- ▷ API SN/CF
- ▷ MB 229.1
- ▷ PSA B71 2295
- ▷ VW 501 01
- ▷ VW 505 00