

SAE 5W30

140105701

GOLD PLATINUM SN/CF SS SAE 5W30

This is a semi-synthetic engine oil that that is developed in order to prevent the engine for building up wear and sludge. It is a so called "universal engine oil" and meets

the latest requirements of most American and Asian passenger cars, SUV's and light vans.



GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	68,3
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	11,6
Viscosity Index	ASTM D2270		166
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,9
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	216
Sulphated ash content	ASTM D874	%	
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	
CCS viscosity @ -35 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

▷ API SN/CF