

SAE 20W

140200201



LOGISTIC TRUCK CF-4 SAE 20W

This is a high quality mineral heavy duty truck engine oil suitable for naturally aspirated or supercharged diesel and gasoline engines. This product is recommended for fixed diesel engines, and mixed fleets of trucks and cars.

The additive technology used in these products ensure long and reliable protection of all the engine parts. These products meet a variety of OEM specifications.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,88
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	54
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	7,6
Viscosity Index	ASTM D2270		103
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6
Pour point	ASTM D6892	°C	-22
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	0,7
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ API CF-4/SG
- ▷ MB 227.0
- ▷ MIL-L-2104 E
- ▷ MIL-L-46152 E