

SAE 15W40

140200601



### LOGISTIC TRUCK CF-4/SG SAE 15W40

This is a high-quality heavy-duty engine oil. This product can be used in 4-stroke gasoline and diesel engines. This product can be used all year round and is intended for the transport and construction sector. This product is particularly suitable for large mixed fleets and can be

used in diesel engines that are naturally aspirated and/or equipped with turbochargers. This formulation includes high detergent and dispersant additives and is specifically developed to function well in extreme working conditions.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,882
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	105
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	13,7
Viscosity Index	ASTM D2270		130
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6,3
Pour point	ASTM D6892	°C	-30
Flash point	ASTM D92	°C	230
Sulphated ash content	ASTM D874	%	0,7
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	6500
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	

### Specifications

- ▷ ALLISON C4
- ▷ API CF-4/SG
- ▷ CATERPILLAR TO-2
- ▷ MAN 271
- ▷ MB 227.1
- ▷ MIL-L-2104 E
- ▷ MIL-L-46152 D
- ▷ VOLVO VDS LEVEL

*All data on this technical data sheet is indicative only.*