

SAE 15W40

140200901



LOGISTIC TRUCK CG-4/SJ E3 SAE 15W40

This is a diesel engine oil that has been made from high quality European base oils and additives. This product is very suitable for the more traditional car portfolio that has usage all-year round. The product enhances longer drain

intervals and complies with EURO II and EURO III emission norms. This product can be used in all modern diesel engines with natural aspiration or turbocharging.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,887
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	101
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	14
Viscosity Index	ASTM D2270		141
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,7
Pour point	ASTM D6892	°C	-33
Flash point	ASTM D92	°C	225
Sulphated ash content	ASTM D874	%	1,27
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	6800
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA A3/B3
- ▷ ACEA A3/B4
- ▷ ACEA E3
- ▷ ALLISON C4
- ▷ MACK EO-L
- ▷ MAN M3275-1
- ▷ MB 228.3
- ▷ MB 229.1
- ▷ VOLVO VDS-2