

SAE 15W50

140203401

LOGISTIC TRUCK CI 4 E7 SAE 15W50

This product is a high-performance diesel engine oil that is developed according to one of the latest emission regulations. This product is suitable for heavily loaded diesel engines. The product can be used in modern diesel engines of trucks, buses, off-road equipment and other heavy-duty materials. This product is highly recommended for diesel engines that meet EURO I, EURO II, EURO III, EURO

IV and EURO V emission requirements. It can be used in vehicles with or without DPF filters and is also applicable in vehicles with SCR NOx reduction systems. It is an excellent product that performs well under extreme operating conditions and increases the lifetime of the equipment. This is a perfect product for the complete fleet.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,881
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	124,2
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	17,6
Viscosity Index	ASTM D2270		156
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	11,1
Pour point	ASTM D6892	°C	-36
Flash point	ASTM D92	°C	>201
Sulphated ash content	ASTM D874	%	1,5
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	7000
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA E7
- ▷ API CI-4
- ▷ API SL
- ▷ CATERPILLAR ECF-1A
- ▷ CUMMINS CES 20077
- ▷ CUMMINS CES 20078
- ▷ DDC 93K215
- ▷ Deutz DQC-III
- ▷ GLOBAL DHD-1
- ▷ JASO DH-1
- ▷ Mach EO-N
- ▷ MAN M3275
- ▷ MB 228.3
- ▷ MTU TYPE 2
- ▷ RENAULT RLD-2
- ▷ VOLVO VDS-3