

This is a 2-stroke engine oil that has been made from the most excellent semi-synthetic base oils. Additives are added that ensure complete engine lubrication. It reduces deposits in the combustion chamber and flushing ports. Also it contains very high cleaning properties in order to clean the spark plugs. This ensures that the engine will keep its power over time. The formulation ensures that there is low to little smoke formation and this product is perfectly suitable for high-speed as well as heavily loaded air-cooled 2-stroke engines. This product can also be used in engines with water cooling/radiator cooling.

Specifications

- ▷ API TC
- ▷ ISO-L-EGC
- \triangleright JASO FC
- ⊳ TISI

| GRADE | METHOD | UNIT | VALUE |
|------------------------------|------------|----------|-------|
| Density @ 15 °C | ASTM D4052 | kg/l | 0,865 |
| Kinematic viscosity @ 40 °C | ASTM D445 | mm2/s | 64,6 |
| Kinematic viscosity @ 100 °C | ASTM D445 | mm2/s | 9,4 |
| Viscosity Index | ASTM D2270 | | 129 |
| B.N. (HCL04 method) | ASTM D2896 | mg KOH/g | 0,9 |
| Pour point | ASTM D6892 | °C | -21 |
| Flash point COC | ASTM D92 | °C | 116 |
| Flash Point PM | | °C | |
| Sulphated ash content | ASTM D874 | % | 0,09 |

All data on this technical data sheet is indicative only.