



SAE 75W80

140601001



MOLINOL GEAR GL-4 ZF SAE 75W80

This is a full synthetic manual transmission gear oil that can be used for manual transmissions of the modern vehicle fleet. It can be used in syncromesh transmissions. This product ensures smooth gear shifting and prolongs the gearbox lifetime. This gear oil meets a variety of spec-

ifications including DAF, Eaton, Volvo, Iveco and Renault. It also includes the Eaton Europe performance standards that include a proven product lifetime of 300.000 km or 3 years. An excellent manual transmission gear oil.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,86
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		154
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	234
CCS viscosity @ -12 °C	ASTM D2983	mPa.s	
CCS viscosity @ -26 °C	ASTM D2983	mPa.s	
CCS viscosity @ -40 °C	ASTM D2983	mPa.s	80000
Copper Corrosion	ASTM D130		

All data on this technical data sheet is indicative only.

Specifications

- ▷ API GL-4
- ▷ DAF MEET REQUIREMENTS
- ▷ EATON EXTENDED DRAIN
- ▷ IVECO MEET REQUIREMENTS
- ▷ MAN 341 E-3
- ▷ MAN 341 Z-4
- ▷ MB 235.4
- ▷ RENAULT B0032/3 AN-NEX 3
- ▷ VOLVO 97305
- ▷ VOLVO 97307
- ▷ ZF TE-ML 01L
- ▷ ZF TE-ML 02L
- ▷ ZF TE-ML 08
- ▷ ZF TE-ML 13
- ▷ ZF TE-ML 16K
- ▷ ZF TE-ML 24A