



SAE 75W90
SS

140602601



MOLINOL GEAR GL-5 SAE 75W90 SS

This is a semi-synthetic GL-5 manual gear oil that is developed for applications where gear shifting problems occur because thicker oils have been used. This product helps to reduce oil degradation and extends the service

life. This gear oil is developed with a high viscosity index that ensures excellent fluidity at low temperatures as well. An excellent product to reduce the current gear shifting problems and extend the lifetime of the vehicle.

Specifications

- ▷ API GL-5
- ▷ MIL MIL-L-2105 D

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,881
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		196
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	206
CCS viscosity @ -12 °C	ASTM D2983	mPa.s	
CCS viscosity @ -26 °C	ASTM D2983	mPa.s	
CCS viscosity @ -40 °C	ASTM D2983	mPa.s	130000
Copper Corrosion	ASTM D130		

All data on this technical data sheet is indicative only.