

AUTOMATIC TRANSMISSION FLUIDS



UNIVERSAL
DEX 3G

140700201



MOLINOL ATF UNIVERSAL DEX 3G

This is a semi-synthetic automatic transmission oil. This product can be used in automatic transmissions, torque converters, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford

Mercon-requirements. This product had a very high viscosity index and is formulated in order to extend the oil lifetime. It ensures excellent low temperature pumpability and extends the transmission lifetime.

GRADE	METHOD	UNIT	VALUE
Colour	Visual		Red
Density @ 15 °C	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		179
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	196
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ ALLISON C4
- ▷ FORD MERCON
- ▷ GM 6147-M
- ▷ GM DEXRON III-G
- ▷ MAN 339 TYP V1
- ▷ MAN 339 TYP Z1
- ▷ MB 236.5
- ▷ MB 236.9
- ▷ VOITH H55.6335xx
- ▷ VOLVO STD 1273,40 (97340)
- ▷ VOLVO STD 1273,41 (97341)
- ▷ ZF TE-ML 03D
- ▷ ZF TE-ML 04D
- ▷ ZF TE-ML 09
- ▷ ZF TE-ML 11A
- ▷ ZF TE-ML 14A
- ▷ ZF TE-ML 17C