

UNIVERSAL
DEX 3H RED

140700301



MOLINOL ATF UNIVERSAL DEX 3H RED

This ATF III-H is a high-quality Automatic Transmission Fluid that is developed from the most solvent base oils. This product can be used in automatic gearboxes that require Dexron III-H lubricants. It is also suitable for power steering systems. This ATF III-H has a very high viscosity index and

offers resistance against corrosion and foam building. It also has good anti-oxidation and anti-wear properties. The low pour point of this ATF III-H ensures that a good protection is offered also at low temperatures and cold starts.

GRADE	METHOD	UNIT	VALUE
Colour	Visual		Red
Density @ 15 °C	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		179
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	196
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ ALLISON C4
- ▷ FORD MERCON
- ▷ GM 6147-M
- ▷ GM DEXRON III-H
- ▷ MAN 339 TYP V1
- ▷ MAN 339 TYP Z1
- ▷ MB 236.5
- ▷ MB 236.9
- ▷ VOITH H55.6335xx
- ▷ VOLVO STD 1273,40 (97340)
- ▷ VOLVO STD 1273,41 (97341)
- ▷ ZF TE-ML 03D
- ▷ ZF TE-ML 04D
- ▷ ZF TE-ML 09
- ▷ ZF TE-ML 11A
- ▷ ZF TE-ML 14A
- ▷ ZF TE-ML 17C