

AUTOMATIC TRANSMISSION FLUIDS



MOLINOL®
PREMIUM GERMAN LUBRICANTS

UNIVERSAL DEX IV

140700501

MOLINOL ATF UNIVERSAL DEX IV

This is a full synthetic automatic transmission fluid for universal applications. This product has a wide range of specifications and can be used in vehicles of a wide range of OEM. This product can be used in the latest generation of

automatic transmissions and torque converters for most passenger cars, small vans and small buses. This product is formulated in order to ensure smooth gear shifting.



GRADE	METHOD	UNIT	VALUE
Colour	Visual		
Density @ 15 °C	ASTM D4052	kg/l	0,847
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		162
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	210
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ AISIN-WARNER AW-1
- ▷ AISIN-WARNER JWS 3324
- ▷ BMW 83222152426
- ▷ BMW M-1375.4
- ▷ CHRYSLER 68157995AA
- ▷ FIAT 9.55550-AV2
- ▷ FIAT 9.55550-AV5
- ▷ FORD MERCON LV
- ▷ FORD MERCON SP
- ▷ FORD WSS-M2C924-A
- ▷ HONDA DW-1
- ▷ HYUNDAI NWS-9638 T5
- ▷ HYUNDAI SP-IV
- ▷ HYUNDAI SPH-IV
- ▷ JAGUAR 02JDE26444
- ▷ LAND ROVER LR023288
- ▷ MAZDA FZ
- ▷ MB 236.12
- ▷ MITSUBISHI ATF J-3
- ▷ NISSAN MATIC-S