

UNIVERSAL
DEX V

140700601



MOLINOL ATF UNIVERSAL DEX V

This is a full synthetic automatic transmission fluid that provides an extreme oxidation stability that ensures low-noise and smooth switching. This product can be used in

European, North American and Asian vehicles. It meets the Ford Mercon V as well as several other specifications.

GRADE	METHOD	UNIT	VALUE
Colour	Visual		
Density @ 15 °C	ASTM D4052	kg/l	0,852
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		176
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	5,8
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	220
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	37,6

All data on this technical data sheet is indicative only.

Specifications

- ▷ ALLISON C4
- ▷ FORD MERCON V
- ▷ JASO 1-A
- ▷ MAN 339 TYP V2
- ▷ MAN 339 TYP Z11
- ▷ MAN 339 TYP Z2
- ▷ MB 236.6
- ▷ VOITH 55.6336
- ▷ VOLVO 97341
- ▷ ZF TE-ML 04D
- ▷ ZF TE-ML 14B
- ▷ ZF TE-ML 16L
- ▷ ZF TE-ML 20B