

AUTOMATIC TRANSMISSION FLUIDS



UNIVERSAL
JP

140700901



MOLINOL ATF UNIVERSAL JP

This automatic transmission fluid is formulated out of the finest full synthetic base oils. This product is suitable for passenger car, off-road and SUV vehicles. It has been specifically developed for American, Japanese as well as

Korean automatic gearboxes. This product meets a large variety of specifications. The excellent oxidation stability and thermal stability ensure that this product has a long lifetime and ensures smooth shifting all year round.

GRADE	METHOD	UNIT	VALUE
Colour	Visual		
Density @ 15 °C	ASTM D4052	kg/l	0,849
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		184
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	218
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ AISIN-WARNER JWS 3309
- ▷ AISIN-WARNER JWS 3314
- ▷ AISIN-WARNER JWS 3317
- ▷ ALLISON TES-295
- ▷ BMW 8072B
- ▷ BMW ETL 7045E
- ▷ BMW LA 2634
- ▷ BMW LT 71141
- ▷ CHRYSLER ATF+3
- ▷ CHRYSLER ATF+4
- ▷ FIAT 9.55550-AV4
- ▷ FORD MERCON V
- ▷ FORD WSS-M2C922-A1
- ▷ HONDA ATF Z-1
- ▷ HYUNDAI SP-III
- ▷ MB 236.10
- ▷ MB 236.11
- ▷ MB 236.3
- ▷ MB 236.7
- ▷ NISSAN MATIC-K