

AUTOMATIC TRANSMISSION FLUIDS



MOLINOL
PREMIUM GERMAN LUBRICANTS

MERC
236.15

140701101



MOLINOL ATF MERC 236.15

This ATF is a fully synthetic Automatic Transmission Fluid specially developed and mandatory for Mercedes Benz 7-speed NAG2FE+ automatic transmissions requiring low viscosity ATF from June 2010. This ATF offers excellent re-

sistance against oxidation, corrosion and foam formation, resulting in a constant high performance during its life-time. NOTE: NOT backwards compatible with previous MB specs; also not for MB 236.10, MB236.12 and MB 236.14.

Specifications

▷ MB 236.15

GRADE	METHOD	UNIT	VALUE
Colour	Visual		
Density @ 15 °C	ASTM D4052	kg/l	0,842
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		172
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-54
Flash point	ASTM D92	°C	178
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.