

AUTOMATIC TRANSMISSION FLUIDS



ZF 8

140701401

MOLINOL ATF ZF 8

This is a full synthetic automatic transmission fluid that is developed for ZF 8HP automatic transmissions. This product can also be used in automatic transmissions with 8HP45, 8HP55, 8HP70 and 8HP90. This automatic transmis-

sion fluid has a superior protection and extends oil and automatic transmission life. It has excellent cold start properties, and contributes to fuel saving.



GRADE	METHOD	UNIT	VALUE
Colour	Visual		
Density @ 15 °C	ASTM D4052	kg/l	0,842
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		190
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	198
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	25,8

All data on this technical data sheet is indicative only.

Specifications

- ▷ BMW 8322 2152426
- ▷ BMW 8322 2289720 (ATF3+)
- ▷ CHRYSLER 68157995AA
- ▷ FIAT 9.55550-AV5
- ▷ JAGUAR 02JDE26444
- ▷ LAND ROVER LR023288
- ▷ VAG G-060-162