

HD

140702201



MOLINOL ATF HD

This is a full synthetic automatic transmission fluid that has been specifically developed for heavy duty vehicles. This product can be used in automatic transmission of heavy duty trucks, buses and off-road equipment. This product has an additive package that ensures exceptional cold

start properties for heavy duty vehicles. The synthetic base oils used in this product ensure long lifetime of the transmission as soot and other deposits are kept to the absolute minimum.

GRADE	METHOD	UNIT	VALUE
Colour	Visual		
Density @ 15 °C	ASTM D4052	kg/l	0,844
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		158
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-54
Flash point	ASTM D92	°C	
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ MAN 339 TYP V1
- ▷ MAN 339 TYP Z3
- ▷ MB 236.9
- ▷ VOITH 55.6335xx
- ▷ VOITH 55.6336xx
- ▷ VOLVO STD 1273,40 (97340)
- ▷ VOLVO STD 1273,41 (97341)
- ▷ ZF TE-ML 04D
- ▷ ZF TE-ML 14C
- ▷ ZF TE-ML 20C